



MAIN-LAND
DEVELOPMENT
CONSULTANTS, INC.

69 MAIN ST. LIVERMORE FALLS, MAINE
367 US ROUTE 1 FALMOUTH, MAINE
PH: (207) 897-6752 FAX: (207) 897-5404
WWW.MAIN-LANDDCI.COM

PROJECT
**SOUTH ST. SIDEWALK
IMPROVEMENT
PROJECT**
SOUTH STREET, BIDDEFORD, ME

OWNER OF RECORD
CITY OF BIDDEFORD

205 MAIN STREET,
BIDDEFORD, ME, 04005

MADE FOR
CITY OF BIDDEFORD

205 MAIN STREET,
BIDDEFORD, ME, 04005

DRAWING SCALE:

NTS

SUBMISSION NOTES:
SUBMISSION 1: 2020-06-09 SDH
ISSUED FOR REVIEW

PROJ. MGR: E.J.
DRAWN BY: SDH
CHECKED BY: E.J.
SUBMISSION NO. N/A
SURVEY DATE: 2020-05-29
SUBMISSION DATE: 2020-06-09
SUBMITTED FOR: REVIEW

NOT FOR CONSTRUCTION

GENERAL NOTES

SEAL:

DRAFT

ERIC J. LABELLE ME PE#7117
DRAWING NO.

C9.2
MLDC NO. 20-083 8 OF 8

EXISTING CONDITIONS AND DEMOLITION

- E1. TOPOGRAPHIC AND BOUNDARY SURVEY INFORMATION SHOWN ON THIS DRAWING PERFORMED AND SUPPLIED BY MAIN-LAND DEVELOPMENT CONSULTANTS, INC (MAIN-LAND).
- E2. RELOCATE EXISTING TBM INFORMATION ONTO NEW TBM OF CONTRACTORS CHOICE FOR CONSTRUCTION USE PRIOR TO REMOVAL OF EXISTING TBM.
- E3. PRIOR TO BEGINNING DEMOLITION OR SITE WORK, THE GENERAL CONTRACTOR SHALL SCHEDULE A PRE-CONSTRUCTION MEETING WITH THE CITY OF BIDDEFORD ENGINEERING DEPARTMENT TO DISCUSS THE INSPECTION PROCESS AND PROJECT SCHEDULE.

SITE LAYOUT AND MATERIALS

- L1. DIMENSIONS ARE TO FACE OF CURB AND TO FACE OF FOUNDATION UNLESS NOTED OTHERWISE.
- L2. PAVEMENT EDGES SHALL BE TRUE TO LINE. SAWCUT EXISTING PAVEMENT IN SMOOTH STRAIGHT LINES WHERE NEW PAVEMENT JOINS. PROVIDE TACK COAT LAYER AS SPECIFIED.
- L3. PROVIDE TRAFFIC CONTROL SIGNAGE AND STRIPING AS SHOWN AND IN ACCORDANCE WITH U.S.D.O.T. MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.

GRADING AND EROSION CONTROL

- G1. ADD 6" LOAM, SEED AND MULCH TO DISTURBED AREAS UNLESS OTHERWISE NOTED. PROVIDE EROSION CONTROL MESH ON ALL SLOPES 6:1 OR STEEPER, AND ALONG DITCH CHANNELS.
- G2. GRADE SURFACES TO DRAIN AWAY FROM BUILDING. PUDDLING OF WATER IN PAVED OR UNPAVED AREAS WILL NOT BE ACCEPTABLE EXCEPT FOR AREAS DESIGNATED AS PONDS.
- G3. MAINTAIN TEMPORARY EROSION CONTROL MEASURES FOR THE FULL DURATION OF CONSTRUCTION. INSPECT WEEKLY AND AFTER EACH STORM AND REPAIR AS NEEDED. REMOVE SEDIMENTS FROM THE SITE, PLACE IN AREA OF LOW EROSION POTENTIAL, AND STABILIZE WITH SEED AND MULCH.
- G4. PLACE TEMPORARY SOIL STABILIZATION WITHIN 7 DAYS OF INITIAL DISTURBANCE. PLACE PERMANENT SOIL STABILIZATION WITHIN 7 DAYS OF FINAL GRADING.

UTILITIES

- U1. THE ACCURACY AND COMPLETENESS OF SUBSURFACE INFORMATION IS NOT GUARANTEED. VERIFY SITE CONDITIONS INCLUDING TEST PITS FOR LOCATIONS AND INVERTS OF UTILITIES AND REPORT ANY DISCREPANCIES TO MAIN-LAND PRIOR TO PROCEEDING WITH THAT PORTION OF THE WORK.
- U2. COORDINATE WORK ON UTILITY LINES OR WITHIN ROAD RIGHT-OF-WAY WITH THE UTILITY COMPANIES AND CITY ROAD DEPARTMENT.

UTILITY LOCATION REQUIREMENTS

PRIOR TO EXCAVATION, VERIFY THE UNDERGROUND UTILITIES, PIPES, STRUCTURES, AND FACILITIES. PROVIDE THE FOLLOWING MINIMUM MEASURES.

- A. PRE-MARK THE BOUNDARIES OF YOUR PLANNED EXCAVATION WITH WHITE PAINT, FLAGS, OR STAKES SO UTILITY CREWS KNOW WHERE TO MARK THEIR LINES.
- B. CALL DIG SAFE, AT 1-888-DIGSAFE, AT LEAST THREE BUSINESS DAYS - BUT NO MORE THAN 30 CALENDAR DAYS - BEFORE STARTING WORK. DON'T ASSUME SOMEONE ELSE WILL MAKE THE CALL.
- D. WAIT THREE BUSINESS DAYS FOR LINES TO BE LOCATED AND MARKED WITH COLOR-CODED PAINT, FLAGS, OR STAKES. NOTE THE COLOR OF THE MARKS AND THE TYPE OF UTILITIES THEY INDICATE. TRANSFER THESE MARKS TO THE AS-BUILT DRAWINGS.
- E. CONTACT THE LANDOWNER AND OTHER 'NON-MEMBER' UTILITIES (WATER, SEWER, GAS, ETC) FOR THEM TO MARK THE LOCATIONS OF THEIR UNDERGROUND FACILITIES. TRANSFER THESE MARKS TO THE AS-BUILT DRAWINGS.
- F. RE-NOTIFY DIG SAFE AND THE NON-MEMBER UTILITIES IF THE DIGGING, DRILLING, OR BLASTING DOES NOT OCCUR WITHIN 30 CALENDAR DAYS, OR IF THE MARKS ARE LOST DUE TO WEATHER CONDITIONS, SITE WORK ACTIVITY, OR ANY OTHER REASON.
- G. HAND DIG WITHIN 18 INCHES IN ANY DIRECTION OF ANY UNDERGROUND LINE UNTIL THE LINE IS EXPOSED. MECHANICAL METHODS MAY BE USED FOR INITIAL SITE PENETRATION, SUCH AS REMOVAL OF PAVEMENT OR ROCK.
- H. DIG SAFE REQUIREMENTS ARE IN ADDITION TO TOWN, CITY, AND/OR STATE D.O.T. STREET OPENING PERMIT REQUIREMENTS.
- I. FOR COMPLETE DIG SAFE REQUIREMENTS, CALL THE P.U.C. OR VISIT THEIR WEBSITE.
- J. IF YOU DAMAGE, DISLOCATE, OR DISTURB ANY UNDERGROUND UTILITY LINE, IMMEDIATELY NOTIFY THE AFFECTED UTILITY. IF DAMAGE CREATES SAFETY CONCERNS, CALL THE FIRE DEPARTMENT AND TAKE IMMEDIATE STEPS TO SAFEGUARD HEALTH AND PROPERTY.
- K. ANY TIME AN UNDERGROUND LINE IS DAMAGED OR DISTURBED, OR IF LINES ARE IMPROPERLY MARKED, YOU MUST FILE AND INCIDENT REPORT WITH THE P.U.C.. FOR AN INCIDENT REPORT FORM VISIT WWW.STATE.ME.US/MPUC OR CALL THE P.U.C. AT 1-800-452-4699.

UTILITY LOCATION REQUIREMENTS

GENERAL NOTES

NOT TO SCALE

NOT TO SCALE

A2

A1